



4320 Tractor



TECHNICAL MANUAL 4320 Tractor

TM1029 (01DEC74) English

John Deere Tractor Works
TM1029 (01DEC74)

LITHO IN U.S.A.
ENGLISH



4320 TRACTOR

TECHNICAL MANUAL

TM-1029 (Aug-70)

CONTENTS

SECTION 10 - GENERAL

- Group 5 - Specifications
- Group 10 - Predelivery, Delivery, and After-Sale Services
- Group 15 - Tune-Up
- Group 20 - Lubrication
- Group 25 - Separation

SECTION 20 - ENGINE

- Group 5 - General Information, Diagnosis, and Tests
- Group 10 - Cylinder Head, Valve Train, and Camshaft
- Group 15 - Cylinder Block, Liners, Pistons, and Rods
- Group 20 - Crankshaft, Main Bearings, and Flywheel
- Group 25 - Lubrication System
- Group 30 - Cooling System

SECTION 30 - FUEL SYSTEM

- Group 5 - Diagnosing Malfunctions
- Group 10 - Fuel Injection System
- Group 15 - Air Intake System

SECTION 40 - ELECTRICAL SYSTEM

- Group 5 - Information and Wiring Diagrams
- Group 10 - Charging Circuit
- Group 15 - Starting Circuit
- Group 20 - Lighting and Accessory Circuits

SECTION 50 - POWER TRAIN

- Group 5 - Syncro-Range Transmission and PTO Clutches
- Group 10 - Syncro-Range Transmission
- Group 15 - Differential
- Group 20 - Final Drive
- Group 25 - PTO
- Group 30 - Power Front-Wheel Drive

SECTION 60 - STEERING AND BRAKES

- Group 5 - General Information

SECTION 70 - HYDRAULIC SYSTEM

- Group 5 - General Information, Diagnosis, and Tests
- Group 10 - Main Reservoir, Filters, Valves, Oil Cooler, and Oil Reservoir
- Group 15 - Hydraulic Pumps
- Group 20 - Power Steering
- Group 25 - Power Brakes
- Group 30 - Rockshaft and Implement Hitches
- Group 35 - Selective Control Valve, Breakaway Couplers, and Remote Cylinders

SECTION 80 - MISCELLANEOUS

- Group 5 - Conventional Front Axle
- Group 10 - Power Front Wheel Drive Axle

Section 10 GENERAL

CONTENTS OF THIS SECTION

	Page		Page
GROUP 5 - SPECIFICATIONS		GROUP 20 - LUBRICATION (Cont.)	
General Tractor Specifications	5-1	Greases	20-2
GROUP 10 - PREDELIVERY, DELIVERY, AND AFTER-SALE SERVICES		Storing Lubricants	20-2
Predelivery Services	10-1	GROUP 25 - SEPARATION	
Delivery Services	10-3	Removing Roll-Gard Cab	25-1
After-Sale Services	10-4	Installing Roll-Gard Cab	25-2
GROUP 15 - TUNE-UP		Separating Engine from Clutch Housing	25-2
Preliminary Engine Testing	15-1	Separating Clutch Housing from Syncro-Range transmission	25-4
Engine Tune-Up	15-1	Removing Engine	25-5
Final Engine Test	15-3	Separating Engine from Front End	25-6
Tractor Tune-Up	15-3	Removing Final Drive Assembly	25-7
GROUP 20 - LUBRICATION		Specifications	25-8
Lubrication Chart	20-1	Torques for Hardware	25-8
Engine Lubricating Oils	20-2	Special Tools	25-8
Transmission-Hydraulic Oil	20-2		

Group 5 GENERAL TRACTOR SPECIFICATIONS

HORSEPOWER:

Observed at PTO 115

ENGINE:

Type 6-cylinder, in-line, valve-in-head,
diesel, turbocharged
Bore and stroke 4-1/4 in. x 4-3/4 in.
Displacement 404 cu. in.
Compression ratio 15.7 to 1
Firing order 1-5-3-6-2-4
Valve clearance Intake-0.018 in.
Exhaust-0.022 in.

Injection pump timing TDC

Engine Speeds:

Working range 1500 to 2200 rpm
Maximum transport speed 2500 rpm
Engine speeds:
Slow idle 800 rpm
1900 rpm load 2150 rpm idle
2200 rpm load 2400 rpm idle
2500 rpm load 2650 rpm idle

LUBRICATION SYSTEM:

Full pressurized
with full-flow micronic oil
filter, water cooled oil
cooler, and bypass valves
for filter and cooler.

FUEL SYSTEM:

Type Direct injection
Filter Two-stage with replaceable
impregnated paper element.
Injection pump type Inlet metering,
distributing type
Air cleaner . . Dry type with safety element

COOLING SYSTEM:

Type Pressurized with centrifugal pump
Temperature control Heavy-duty
thermostat

CAPACITIES:

Fuel tank 44 U.S. gals.
Cooling system 28 U.S. qts.
Crankcase (with filter change) 16 U.S. qts.
Transmission-hydraulic system (add 4-1/2
gals. to capacity if equipped with Power Front
Wheel Drive) 14 U.S. gals.

TRANSMISSION:

Type Syncro-Range, constant mesh
Clutch Heavy-duty, 13-1/2 in. plate,
foot operated
Gear selections 8 forward and 2 reverse
Shifting 4 stations, synchronized
forward shifting within stations

POWER TAKE-OFF:

Type Single 1-3/8-inch PTO shaft with
rear power take-off.
Speed (1900 engine rpm) 540 or 1000 rpm
Rear PTO Ahead of Drawbar Hitch Point:
540 rpm 14 in.
1000 rpm 16 in.

HYDRAULIC SYSTEM:

Type Closed center, constant pressure.
Actuates power steering, power
brakes, Power Front Wheel Drive,
and implement control.
Standby pressure 2250 psi

BRAKES Hydraulically power actuated,
disk-type operating in oil
Provision for manual operation
with brake accumulator
to supply oil.

STEERING Full power, hydrostatic type.
Provision for manual operation.

ELECTRICAL SYSTEM:

Type 12-volt, negative ground
Alternator 12-volt, 55 amps
Air Conditioned tractors 12-volt, 72 amps
Battery Two, 6-volt, 75-plate 172-
ampere-hour

FRONT TIRES* 7.5L-15, 6-ply

REAR TIRES* 20.8-34, 10-ply

FRONT WHEEL TREAD 51 to 80 in.

REAR WHEEL TREAD:

18.4-38 tire, regular axle 60 to 91 in.

* Additional tire sizes available.

* * Tractors with air conditioned
cabs and 18.4-34 tires.

GROUND SPEEDS IN MILES PER HOUR (2200 engine rpm and with 18.4-38 rear tires):

Gear	
1st	1.9
2nd	3.0
3rd	4.0
4th	5.1
5th	6.4
6th	8.3
7th	10.9
8th	17.7
1st reverse	3.9
2nd reverse	6.2

POWER FRONT-WHEEL DRIVE:

Type Hydraulic motor driven with planetary gear reduction in wheel hub, uses pressure oil from hydraulic system
Torque Low (series connected) and high (parallel connected)
Controls Solenoid operated control valves, synchronized with transmission controls
Planetary disconnect Hydraulic wet brake on ring gear releases when drive is disengaged

DIMENSIONS:

Wheelbase (Subtract 1 inch for tractors equipped with Power Front-Wheel Drive) 106-1/2 in.
Over-all length 159-1/2 in.
Over-all height* 113 in.
Height to steering wheel 81-1/2 in.
Over-all width 89-3/4 in.
Turning radius
Without Power Front Wheel Drive (minimum tread and brakes applied) 136 in.
Power Front Wheel Drive (with drive engaged in "High Torque", brakes applied and minimum wheel tread) 126 in.

SHIPPING WEIGHT (With equipment for average field service, less fuel and ballast). Add 385 lbs. if equipped with Roll Gard. Add 1,000 lbs. for Power Front-Wheel Drive
Row-Crop 9,050 lbs.
Standard 9,070 lbs.

(Specifications and design subject to change without notice.)

Group 10 PREDELIVERY, DELIVERY, AND AFTER-SALE SERVICES

PREDELIVERY SERVICE

Because of the shipping factors involved, plus extra finishing touches that are necessary to promote customer satisfaction, proper predelivery service is of prime importance to the dealer.

A tag pointing out the factory-recommended procedure for predelivery service is attached to each new tractor before it leaves the factory.

After completing the factory-recommended dealer checks and services listed on the predelivery tag, remove the tag from the tractor and file it with the shop order for the job. The tag will certify that the tractor has received the proper predelivery service when that portion of the customer's John Deere Delivery Receipt is completed.

NOTE: A Caplug is placed in the muffler outlet to prevent turbocharger rotation during transit. Remove Caplug before unloading tractor. Reinstall Caplug before transporting the tractor to the customer.

TEMPORARY TRACTOR STORAGE

Service	Specification	Reference
Check radiator for coolant loss and antifreeze protection	2 inches above baffle.
Reduce shipping pressure of tires	Operator's manual
Cover tractor and tires for protection and cleanliness

BEFORE DELIVERING TRACTOR

ELECTRICAL SYSTEM		
Install electrolyte and charge batteries	FOS-20 Manual —ELECTRICAL SYSTEMS
Stamp date code on battery	FOS-20 Manual —ELECTRICAL SYSTEMS
Connect alternator. Do not attempt to polarize.	Section 40, Group 10
Connect Power Front-Wheel Drive wiring harness at connector near control valves	Section 40, Group 5
Install light switch knob
Clean terminals and connect battery cables	Section 40, Group 5
Check alternator belt tension	1-inch deflection, 25 lb. force; 1-inch deflection, 20 lb. force on air conditioned tractors.	Operator's manual

BEFORE DELIVERING TRACTOR—Continued

Service	Specification	Reference
COOLING SYSTEM		
Inspect radiator for coolant loss	2 inches above baffle.
Check antifreeze protection
TIRES AND WHEELS		
Adjust pressure of tires	Operator's manual
Check front wheel hub bolts, rear wheel rim clamp nuts, and rear wheel retainer cap screws for tightness	Front hub bolts - 85 ft-lbs Rear hub bolts - 300 ft-lbs Rim clamp nuts - 170 ft-lbs
LUBRICATION		
Check crankcase oil level	To upper marks on dipstick.	Operator's manual
Check transmission-hydraulic system oil level	To top of "SAFE" range on dipstick. Type 303 Special-Purpose Oil.	Operator's manual
Lubricate grease fittings	SAE multipurpose-type grease.	Operator's manual
ENGINE		
Check air cleaner	Operator's manual
Fill fuel tank and start engine	Capacity - 44 U.S. gallons	Operator's manual
Check operation of starter, alternator, flasher, gauges, and indicator lights	Operator's manual
Check engine timing	TDC	Section 30, Group 10
Check engine speeds	800 rpm, slow idle speed 2650 rpm idle speed, 2500 max. transport speed	Section 30, Group 10
OPERATION		
Check transmission clutch free travel	Approximately 1-1/2-inch free travel (at least 3/4 in.).	Operator's manual
Shift transmission through all speeds	Operator's manual
Check throttle linkage for free operation	Section 30, Group 10
Adjust headlights and check operation	Operator's manual

BEFORE DELIVERING TRACTOR—Continued

Service	Specification	Reference
Check Power Front-Wheel Drive operation	Operator's manual
Check power takeoff operation	Operator's manual
Check differential lock operation	Operator's manual
Check brakes and accumulator	3 in. maximum travel for one emergency application immediately after stopping engine.	Operator's manual
Check hydraulic system operation: Rockshaft, steering, and remote cylinder	Operator's manual
Check operation of air conditioning system and heater system	Operator's manual
Check air conditioner compressor drive belt	1/4 in. deflection, 15 lb. pull	Operator's manual
Check implement hitch operation	Operator's manual
Check seat operation	Operator's manual
GENERAL		
Tighten accessible nuts and cap screws
Clean tractor and touch up paint

DELIVERY SERVICE

A thorough discussion of the operation and service of a new tractor at the time of delivery helps to assure complete customer satisfaction. Proper delivery should be an important phase of a dealer's program. A portion of the John Deere Delivery Receipt emphasizes the importance of proper delivery service.

Many complaints have arisen simply because the owner was not shown how to operate and service his new tractor properly. Enough time should be devoted, at the customer's convenience, to introducing the owner to his new tractor and explaining to him how to operate and service it.

IMPORTANT: Install Caplug in muffler outlet if transporting tractor to customer. This will prevent damage to the turbocharger caused by air passing through the turbocharger and rotating it without lubrication when the engine is stopped.

The following procedure is recommended before the serviceman and owner complete the delivery acknowledgments portion of the delivery receipt.

Using the tractor operator's manual as a guide, be sure that the owner understands these points thoroughly:

1. Controls and instruments.
2. How to start and stop the engine.
3. The importance of the break-in period.
4. How to use liquid or cast-iron ballast.
5. All functions of the hydraulic system.
6. Using the power takeoff.
7. The importance of safety.
8. The importance of lubrication and periodic services.

After explaining and demonstrating the above features, have the owner sign the delivery receipt and give him the operator's manual.

AFTER-SALE INSPECTION

The purchaser of a new John Deere tractor is entitled to a free inspection within the warranty period after the equipment has been "run-in". The terms of this after-sale inspection are outlined on the back of the John Deere Delivery Receipt.

The purpose of this inspection is to make sure that the customer is receiving satisfactory performance from his tractor. At the same time, the inspection should reveal whether or not the tractor is being operated, lubricated, and serviced properly.

If the recommended after-sale service inspection is followed, the dealer can eliminate a needless volume of service work by preventing minor irregularities from developing into serious problems later on. This will promote strong dealer-customer relations and present the dealer an opportunity to answer questions that may have arisen during the first few days of operation. During the inspection service, the dealer has the further opportunity of promoting the possible sale of other new equipment.

The following inspection program is recommended within the first 100 hours of tractor operation.

INSPECTION PROCEDURE

Service	Specification	Reference
COOLING SYSTEM		
Check radiator coolant level	2 inches above baffle.
Clean external surface of radiator core
Check hoses and connections for leaks
FUEL SYSTEM		
Remove water and foreign matter from filter sediment bowl	Operator's manual
Bleed fuel system	Operator's manual
Tighten loose connections and check entire system for leaks. Correct if necessary
Check air cleaner element, and unloading valve. Clean element if necessary	Operator's manual
ELECTRICAL SYSTEM		
Check specific gravity of battery(s)	Full charge - 1.260 at 80°F.	Operator's manual
Check level of battery electrolyte	To bottom of filler neck in each cell.	Operator's manual
Check belt tension	1-inch deflection with a 25-pound force.	Operator's manual
	1-inch deflection with a 20-pound force on air conditioned tractors.	




INSPECTION PROCEDURES—Continued

Service	Specification	Reference
Start engine and check operation of starter, lights, and indicator lamps	Operator's manual
LUBRICATION		
Check crankcase oil level	To upper marks on dipstick.	Operator's manual
Check Transmission-hydraulic system oil level	In "SAFE" range on dipstick. Use John Deere Type 303 Special-Purpose Oil.	Operator's manual
ENGINE		
Check valve clearance	Intake - 0.018 inch Exhaust - 0.022 inch	Operator's manual
Check engine speed under load, fuel consumption, and horsepower	Specification.	Group 15 of this Section.
CLUTCHES AND DIFFERENTIAL LOCK		
Check transmission clutch free travel	Approximately 1-1/2 inch free travel.	Operator's manual
Shift transmission through all speeds	Operator's manual
Check Power Front-Wheel Drive operation	Operator's manual
Check PTO clutch and brake operation	Section 50, Groups 35 & 40
Check differential lock operation	Operator's manual

INSPECTION PROCEDURES—Continued

Service	Specification	Reference
HYDRAULIC SYSTEM		
Check rockshaft and remote cylinder operation	Section 70, Group 30
3-point hitch negative stop adjustment	1/8th turn back out after contacting transmission case.	Section 70, Group 30
Check power steering	Smooth, easy operation.	Section 70, Group 20
Check brakes and accumulator	3 in. maximum travel for one emergency application immediately after stopping engine.	Operator's manual
AIR CONDITIONING		
Check operation of air conditioning system and heating system	Operator's manual
Check air conditioner compressor drive belt tension	1/4 in. deflection 15 lb. pull	Operator's manual
NUTS AND CAP SCREWS		
Tighten accessible nuts and cap screws that seem to require adjustment.

RECOMMENDED TORQUE IN FOOT-POUNDS

			
Bolt Diameter	Plain Head*	Three Radial Dashes*	Six Radial Dashes*
1/4	6	10	14
5/16	13	20	30
3/8	23	35	50
7/16	35	55	80
1/2	55	85	120
9/16	75	130	175
5/8	105	170	240
3/4	185	300	425
7/8	160	445	685
1	250	670	1030

* The types of bolts and cap screws are identified by head markings as follows:

Plain Head: regular machine bolts and cap screws.

3-Dash Head: tempered steel high-strength bolts and cap screws.

6-Dash Head: tempered steel extra high-strength bolts and cap screws.

Group 15

TUNE-UP

Before tuning up a tractor, determine whether a tune-up will restore operating efficiency. When there is doubt, the following preliminary tests will help to determine if the engine can be tuned up. If the condi-

tion is satisfactory, proceed with the tune-up. Choose from the following procedures only those necessary to restore the unit.

PRELIMINARY ENGINE TESTING

Operation	Specification	Section-Group Reference
Dynamometer Test (at 2200 engine rpm)	Compare with previous recorded output; compare with output after tune-up.	FOS - 30 Manual—ENGINES, Chapter 12
Compression Test	385-410 psi at 215-245 rpm.	FOS - 30 Manual—ENGINES, Chapter 12
Engine Coolant Check Test	No air bubbles or oil film in radiator.	FOS - 30 Manual—ENGINES, Chapter 12

ENGINE TUNE-UP

Operation	Specification	Section-Group Reference
Air Intake System Service air cleaner and check system for leaks	FOS - 30 Manual—ENGINES, Chapter 12
Check system for restrictions using water manometer (inches of water)	FOS - 30 Manual—ENGINES, Chapter 12
Normal reading (with clean filter elements)	8 in. at 2200 rpm
Maximum permitted reading	25 in. at 2200 rpm
Check restriction indicator light operation	24-26 in. at 2200 rpm
Check manifold pressure	12.2-15 psi
Exhaust System Check system for leaks	FOS - 30 Manual—ENGINES, Chapter 12
Check muffler and exhaust pipe for restrictions	FOS - 30 Manual—ENGINES, Chapter 12

ENGINE TUNE-UP—Continued

Operation	Specification	Section-Group Reference
Crankcase Ventilating System Check system for restrictions	FOS - 30 Manual— ENGINES, Chapter 12
Cooling System		
Clean grille screen, radiator core, and oil cooler core	20-30
Clean and flush system; check thermostat	Starts to open-177°F. to 182°F.	20-30
Check pressure cap	6.25 to 7.50 psi release pressure	20-30
Cylinder Head and Valves		
Torque cylinder head cap screws	130 ft-lbs in sequence	20-10
Set valve clearance	Intake - 0.018 in. Exhaust - 0.022 in.	20-10
Diesel Fuel System		
Check fuel tank for water	30-10
Check fuel pump pressure	3-1/2 to 4-1/2 psi	30-10
Drain sediment bowl and change filter	30-10
Service injection nozzles	30-10
Injection Pump:		
Service and check timing	TDC	30-10
	5° advance at 1900 rpm (full load)	30-10
Adjust throttle linkage	2650 rpm high idle speed, 2500 max. transport speed 2150 rpm idle speed, 1900 load speed 2400 rpm idle speed, 2200 load speed 800 rpm, slow idle speed	30-10
Lubrication system		
Check engine oil pressure	40 to 50 psi (1900 rpm)	20-25
Charging System		
Check battery specific gravity	1.240 - 1.260	40-10
Check battery water consump- tion and electrolyte level	40-10
Clean battery, cables, and box	40-10
Check alternator belt tension	25 lbs. at 1 in. belt deflection; 20 lbs. at 1 in. belt deflection on air con- ditioned tractors	40-10
Check alternator output	45 amps at 1440 engine rpm (13-15 volts) on 55 amp alternators; 65 amps at 1400 engine rpm (13-15 volts) on 72 amp alternators	40-10
Check alternator regulated voltage	14.2 to 14.6 volts (operating)	40-10

ENGINE TUNE-UP—Continued

Operation	Specification	Section-Group Reference
Starting System		
Check start-safety switch operation	40-15
Check battery voltage when starting	Min. 9 volts (cranking)	40-15
Check starter current draw ...	Diesel - approx. 400 amps	40-15
Check operation of alternator and oil pressure indicator lights	40-25

FINAL ENGINE TEST

Operation	Specification	Section-Group Reference
Dynamometer Test (at 2400 engine rpm)	Compare with previous recorded output; record for future use.	FOS - 30 Manual— ENGINES, Chapter 12

TRACTOR TUNE-UP

Operation	Specification	Section-Group Reference
Adjust transmission clutch free travel	1-1/2 in.	50-5
Transmission		
Check shifting	50-10
Check for proper operation without excessive noise	50-10 & 15
Check differential lock operation	420 to 480 psi	50-15
Check brake pedal travel and even position	3 in. max. for one emergency application immediately after stopping engine	70-25
Check front wheel bearing adjustment and lubrication	35-ft.-lbs; back-off to nearest hole
Check front wheel toe-in	1/8 to 3/8 in.
Check tire inflation	Operator's Manual

TRACTOR TUNE-UP—Continued

Operation	Specification	Section-Group Reference
Check Power Front-Wheel Drive operation	50-30
Transmission pump	9 gpm at 1900 rpm	70-5
Main hydraulic pump	Standby - 2200 - 2300 psi (2300 psi for Power Front-Wheel Drive) Capacity - 22 gpm (2000 psi and 1900 rpm)	70-5
Pressure control valve	1650 - 1700 psi at 800 rpm (approximately 5 gpm flow)	70-5
Rockshaft:		
Lift cycle time (75 degrees rotation)	1.9 - 2.2 seconds at 1900 rpm	70-30
Maximum oil flow	10.5 to 11.5 gpm at 2000 psi and 1900 rpm	70-30
Lever position (depth control) .	Complete raise at 1/32-inch from end of slot	70-30
Lever position (load control) ..	0 of quadrant to raise (rear lever edge)	
Negative stop adjustment	1/8th turn back out after contacting transmission case	70-30
Selective control valve	2 to 12-1/2 gpm at 1500 psi and 1900 rpm	70-5
Power Front-Wheel Drive pressure control	1900 - 2000 psi at 1200 rpm, 4th gear, high torque, and 2 gpm flow through jumper hose at breakaway coupler	50-30
Hydraulic system pressures, flow rates, or cycle times are for conditions specified in Section 70 (tractor at operating temperature, transmission-hydraulic oil at 140°F. to 160°F., proper test equipment, correct test sequence, etc.).		

Group 20 LUBRICATION

GENERAL INFORMATION

Carefully written and illustrated instructions are included in the tractor operator's manual. Remind your customer to follow the recommendations in these instructions.

For your convenience when servicing the tractor, the following chart showing capacities and type of lubricant for the various components has been included. Additional lubrication information is on page 20-2.

Component	Capacity	Type of Lubricant	Interval of Service
Engine Crankcase	16 U.S. quarts (includes filter)	See "Engine Lubricating Oils" on page 10-20-2	10 Hours - Check level 100 Hours - Change oil 200 Hours - Replace filter
Transmission and Hydraulic System	* 18 U.S. gallons	John Deere Type 303 Special-Purpose Oil	200 Hours - Check level 600 Hours - Replace filter 1200 Hours - Change Oil
Front Wheel Bearings	Wheel Bearing Grease	1200 Hours - Repack bearings
Grease Fittings	SAE Multipurpose-type Grease	See Operator's Manual

* Add 4-1/2 gals. to capacity if equipped with Power Front-Wheel Drive.

Please click here and go
back to our website.

BUY NOW

Then Instant Download the
Complete Manual.

Thank you very much!